

ToughTek™ Mortar Equipment

Reliable Equipment for Mortar Applications



PROVEN QUALITY. LEADING TECHNOLOGY.

Rely on ToughTek Equipment

► Rugged, Dependable Equipment Solutions



Pumps					
MODEL	F340e	F680e	M680a	P15	P25
Type	Piston Pump	Piston Pump	Piston Pump	Progressive Cavity	Progressive Cavity
Max Particle Size	1/8 in (3 mm)	1/8 in (3 mm)	1/8 in (3 mm)	1/8 in (3 mm)	1/4 in (6 mm)
Flow rate (gpm, lpm)	6.5 gpm (24 lpm)	10.8 gpm (41 lpm)	10.8 gpm (41 lpm)	3.6 gpm (14 lpm)	10.0 gpm (38 lpm)
Output - Fireproofing	15 bags/hour	25 bags/hour	25 bags/hour	NA	NA
Output - Underlayment	NA	NA	NA	NA	200 bags/hour
Applications	Fireproofing Self-leveling Underlayment Plaster Stucco EIFS	Fireproofing Self-leveling Underlayment Mortar Plaster	Fireproofing Self-leveling Underlayment Mortar Epoxy-based Mortar Waterproofing Epoxy Cladding Non-slip Coatings	Fireproofing Self-leveling Underlayment Mortar Plaster Stucco EIFS	Fireproofing Self-leveling Underlayment Mortar Plaster Stucco EIFS
Power	110V, 15A 230V, 10A, 1ph	230V, XXA, 1ph (no compressor) 230V, 30A, 1ph (with compressor) 380V, XXA, 3ph (no compressor) 380V, XXA, 3ph (with compressor)	40 CFM air compressor (pneumatic pump)	110V, 20A	230V, 30A, 1ph 230V, 30A, 3ph



Pumps		Mixer Pump	Mixers	
P25X	P35	MP25	D25	D35
Progressive Cavity	Progressive Cavity	Progressive Cavity	Continuous Mixer	Continuous Mixer
1/4 in (6 mm)	5/16 in (8 mm)	1/8 in (3 mm)	1/4 in (6 mm)	5/16 in (8 mm)
10.0 gpm (38 lpm)	18.7 gpm (71 lpm)	6.2 gpm (23.5 lpm) (S0) 12.4 gpm (47 lpm) (H0)	10.0 gpm (38 lpm)	21.0 gpm (80 lpm)
NA	NA	NA	NA	NA
200 bags/hour	300 bags/hour	100 bags/hour 200 bags/hour	140 bags/hour	300 bags/hour
Fireproofing Self-leveling Underlayment Mortar Plaster Stucco EIFS	Fireproofing Self-leveling Underlayment Mortar Plaster Stucco EIFS	Fireproofing Self-leveling Underlayment Mortar Plaster Grout	Self-leveling Underlayment Mortar Plaster Stucco EIFS	Self-leveling Underlayment Mortar Plaster Stucco EIFS
230V, 30A, 1ph	230V, 30A, 3ph	230V, 30A, 1ph (Standard Output) 230V, 30A, 3ph (High Output)	230V, 30A, 1ph 230V, 30A, 3ph	230V, 30A, 1ph 230V, 30A, 3ph



ABOUT GRACO

PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA

Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM

European Headquarters
Graco BVBA
Industrieterrein-Oude Bunders
Slakweidestraat 31
3630 Maasmechelen,
Belgium
Tel: 32 89 770 700
Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tel: 61 3 9468 8500
Fax: 61 3 9468 8599

CHINA

Graco Hong Kong Ltd.
Shanghai Representative Office
Building 7
1029 Zhongshan Road South
Huangpu District
Shanghai 200011
The People's Republic of China
Tel: 86 21 694 50088
Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd.
India Liaison Office
Room 443, Augusta Point
Golf Course Road
Gurgaon, Haryana
India 122001
Tel: 91 124 435 4030
Fax: 91 124 435 4001

JAPAN

Graco K.K.
1-27-12 Hayabuchi
Tsuzuki-ku
Yokohama City, Japan 2240025
Tel: 81 45 593 7300
Fax: 81 45 593 7301

KOREA

Graco Korea Inc.
Shinhan Bank Building
4th Floor #1599
Gwanyang-Dong, Dongan-Ku,
Anyang-si, Korea 431-060
Tel: 82 31 476 9400
Fax: 82 31 476 9801

SALES/ DISTRIBUTION/ SERVICE

Call today for product information or to request a demonstration.

877-84GRACO (1-877-844-7226) or visit us at www.graco.com.

Graco Inc. is registered to I.S. EN ISO 9001

North America
Customer Service
800-328-0211
Fax 877-340-6427



©2015 Graco Inc. ELECTRONIC ONLY 349539 Rev. A 9/15 All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. All other brand names or marks are used for identification purposes and are trademarks of their respective owners.